

## OVERVIEW









Millennium Tiles are a unique premium stainless steel tile that will offer your façade or roof what no other material can do ..... Colour. Millennium Tiles are prismatically coloured stainless steel which means they reflect different colours and light depending on viewing angle and sunlight. In other words, when you walk past a Millennium Tiles project the tiles magically

change colour offering a unique appearance no other material can match.





Beautiful maintenance free metal tiles are available in either natural or prismatic stainless steel versions. The colour will not fade, crack, peel or be affected by UV.



## FEATURES

-  Beautiful changing colour design
-  Lightweight interlocking tile design
-  Easy to install
-  Vertical, horizontal and diagonal installation
-  Can be used for roofing (15 degs & above) or cladding applications
-  Concealed clips and fasteners
-  Excellent wind resistance
-  Available in flat or cupped tiles for added appearance.

## MATERIALS

-  STAINLESS STEEL
-  ZALMAG
-  ALUMINIUM
-  COPPER

### ADDRESS

3/328 Brisbane Rd, Labrador QLD 4214

### TELEPHONE

+61 7 5537 1937

### EMAIL

info@euroclad.com.au

### ABN

45 297 371 439



## INSTALLATION

- 20mm continuous air gap must be beneath the plywood substrate for ventilation
- Proctor breathable wall wrap fixed to outer plywood substrate
- Millennium Tiles are installed on a minimum 15mm plywood substrate ('other' substrates are available for buildings with strict fire codes)
- Interlocking tile attached directly into plywood substrate

## APPLICATIONS

- Facades
- Soffits
- Wall Cladding
- Roofing



\*\*Metal cladding/roofing and especially lengthy flat-span sheet-metal panels often will exhibit waviness, commonly referred to as "oil-canning." The degree of oil-canning and the appearance of the panels will vary depending on factors such as the length and colour of the panels, alloy, gauge, substrate condition and exposure to sunlight. Oil-canning pertains to aesthetics and not the performance of the panels and is not controlled by the contractor. The type of metal roofing panels specified can affect the degree of oil-canning. Euroclad is not responsible for oil-canning or aesthetics. Oil-canning shall not be grounds to withhold payment or reject panels of the type specified. For more information please contact Euroclad.

### ADDRESS

3/328 Brisbane Rd, Labrador QLD 4214

### TELEPHONE

+61 7 5537 1937

### EMAIL

info@euroclad.com.au

### ABN

45 297 371 439